

HALI-BRITE®

RCM-D

L-893 Runway Closure Marker

Compliance with Standards:

ETL Certified to FAA AC 150/5345-55A
with FAA AC 150/5370-2 and NTSB
Safety Recommendation A-03-05

Applications:

The Hali-Brite Runway Closure Marker is an effective method to warn pilots of closed runways and taxiways.

Features:

- Easily set up by one person in 2-3 minutes, without tools
- 3 year/3000 hour engine warranty
- Four folding arms open to 14 foot length
- 20 PAR lamps deliver over 144,000 candelas at beam center
- Visible 10-25 miles from runway under VFR
- Selectable brightness levels to suit environmental conditions
- Photocell dimming for night operation
- Four rear-mounted lamps allow visual monitoring from rear side
- Powered by a three-cylinder, liquid cooled Mitsubishi diesel engine and Marathon brushless generator
- Operates 140 hours between fuel fills
- Highway towable, with a standard 2" hitch coupler
- 2200 pound, DOT compliant trailer
- 4 swivel leveling jacks
- Adjustable light beam angle
- Optional rear hitch, allows tandem towing of 2 units
- Optional cover



HALI-BRITE® INC.

P.O. BOX 10 • 925 1st ST SW

CROSBY, MN 56441

PHONE 1-800-553-6269 OR 218-546-7473 • FAX 218-546-6854

www.halibrite.com

HALI-BRITE®

Set Up Procedure (2-3 minutes):



1. Level as necessary using 3 leveling jacks



2. Extend the 4 light assembly arms.



3. Tilt the light to the upright position.



4. Start the generator and activate the lights.

Light Assembly Specifications:


- Arm length 14 feet when operating
- Hinged to generator housing, swings upright for use, swings to horizontal position when stowed
- Assembly arms fold to a 5'x5' square for transport and storage
- Arms constructed of 4"x4" extruded aluminum, with yellow epoxy powder-coat paint.
- Twenty 90-watt halogen lamps mounted in front, plus 4 monitor lamps in rear, 24 total
- PAR 38 halogen lamp, 25 degree beamwidth, rated life 6000 hours
- Lamps flash 2.5 seconds on, 2.5 seconds off
- Solid-state flasher, no mechanical contacts
- Photocell automatically reduces intensity at night
- 2-year warranty on light assembly, excluding lamps

Trailer Specifications:

- 2200 pound axle
- 2" ball or optional pintle hitch, safety chains
- Four 2000 lb. leveling jacks. Side jacks are on extendable 38" outriggers
- DOT-compliant tail and marker lights
- Tires - ST175/80 D13, highway-rated
- All steel tubing construction
- Width: 67 inches
- Length: 105 inches
- Height: 64 inches
- Total wet weight 1600 lbs.

Engine and Generator Specifications:

- Engine: Mitsubishi L3E Diesel, 12.7 hp, 3-cylinder, liquid-cooled, 4-stroke, 1800 RPM, electric start
- Engine Warranty: 2 years/2000 hours on entire engine, 3 years/3000 hours on major components
- Glow plugs and elapsed hour meter
- Low oil/high temperature auto-shutdown
- Generator: Marathon Electric, 6.0 kW, 120 VAC, 4-pole, brushless
- Fuel tank capacity 57 gal., consumption 0.4 gph, 140 hour runtime



HALI-BRITE® INC.

P.O. BOX 10 • 925 1st ST SW
CROSBY, MN 56441

PHONE 1-800-553-6269 OR 218-546-7473 • FAX 218-546-6854
www.halibrite.com